

Supersedes 4.705.25

**Version:**

Stator with 6 x M20 thread bc Ø 200 mm  
 Suitable for both clamshell buckets and grapples  
 Version: 3000/6000 psi

**Machine:**

e. g. hydraulic excavators - service weight:  
 With gimbal mounting up to 14 t (20 t)

**Work attachments:**

Clamshell buckets up to 0.9 m<sup>3</sup>  
 Grapples up to 0.4 m<sup>3</sup>  
 Special equipment (please consult with manufacturer)

**Specifications:**

Max. axial load	= 60 kN
Pmax. gripper	= 320 bar
Pmax. rotating motor	= 200 bar
Torque/100 bar	= 600 Nm
Displacement	= 500 cm <sup>3</sup> /r
Min. oil passage Gs/Go	= NW 14
Mass	= 75 kg
Max. rotating speed	= 30 r/min


Max. bending moment on request


**Scope of delivery:**

1x plug screw G 3/4"  
 (for plugging of third connection)

**Connections:**

R1, R2: Turn rotator  G 1/2"

Go: Open gripper   
 Stator G 1"  
 Housing: SAE 1" 3000 psi and G 3/4"  
 (on request SAE 1 1/4" 6000 psi and G1" available)

Gs: Close gripper   
 Stator: G 1"  
 Housing: SAE 1" 3000 psi and G 3/4"  
 (on request SAE 1 1/4" 6000 psi and G1" available)

Issue **092** Gm.

Painting: prime-coated in black  
 All changes reserved!  
 Proprietary, no reprinting allowed!

