

- Safe connection by means of long fastening screws
- High permissible axial loads
- Amply dimensioned oil passage
- High torque
- Long service life
- Compact build

Special version:

(for excavator operation)

6 fastening screws M20 DIN 912
 Special hole circle: $\varnothing 180$

Machine:

e. g. heavy-duty hydraulic excavators ,
 heavy-duty forestry cranes

Work attachments:

Heavy-duty gripper saws
 Special equipment (please consult with manufacturer)

Specifications:

Max. axial load = 120 KN
 Max. radial load on request
 Pmax. gripper/saw = 350 bar
 Pmax. rotating motor = 250 bbar
 Torque/100 bar = 1000 Nm
 Displacement = 700 cm³/r
 Min. oil passage Gs/Go = NW 10
 Min. oil passage S1/S2 = NW 14
 Mass = 60 kg
 Max. rotating speed = 30 r/min





Accessories:

Suspension forks
 Single-acting and double-acting swing brakes
 (see separate dimension sheets)

Scope of delivery:

1 x Hose protection with screws
 2 x Connex pin SG 16 x 30
 6 x Cylinder screws M20 x 190-10.9 DIN 912
 6 x Hex nuts M20 DIN 6331

Connections:

R1, R2: Turn rotator		G 1/2"
Go: Open gripper		G 1/2"
Gs: Close gripper		G 1/2"
S1, S2: Saw		G 3/4"

Issue 4/00

Painting: prime-coated in black
 All changes reserved!
 Proprietary, no reprinting allowed!

