

Variant design:

Star flange 140x140 for M16 screws with 2 axial and 2 radial connections G 3/8"

Machine:

e.g. hydraulic excavator service weight:
 max. 3,0ts with floating attachment
 max. 1,8ts with rigid attachment

Add-on units:

Clamshell buckets of max. 0,25m³
 Grapples of max. 0,10m³
 Grabs for demolition and sorting
 of max. 0,10ts dead load
 Sorting units (please ask manufacturer)

Technical details:

max. thrust load	= 20KN
max. radial load	= 12KN
Pmax. grab	= 32MPa
Pmax. rotating engine	= 20MPa
Torque / 1 MPa	= 30Nm
Absorption volume	= 260cm ³ /R
min. oil passage Gs/Go	= NW8
Mass	= 13,5kg
max. rotations	= 30rpm

max.transverse moment: refer to 4.602.00





Volume of delivery:

2 Screw plug	G 3/8"
2 Connex pin	SG 13x20

Accessories:

suspension

Connections:

R1,R2: turn rotator	 G 3/8"
Go: open grab	 G 3/8"
Gs: close grab	 G 3/8"
L: Measuring conn.	 G 1/4"

Edition 073 Gm.

Paint: black primary coat

Reserve made to modifications

All rights reserved