

Variants of design:

Stator with scew thread 12xM20 \varnothing 220
 Pattern of holes not symmetrical
 Fitting dimensions same as:
 712HC-1-G1" and 712HC-3-G1"

Machine:

e.g. hydraulic excavator service weight:
 max. 29ts. with floating attachment
 max. 21ts. with rigid attachment

Add-on units:

Clamshell buckets of max. 1.9m³
 Grapples of max. 0.75m³
 Grabs for demolition and sorting
 of max. 1.1ts. dead load
 Sorting units (please ask manufacturer)

Technical details:





max. thrust load	- 150KN
max. radial load	- 110KN
Pmax. grab	- 35MPa
Pmax. rotating engine	- 25MPa
Torque/1 MPa	- 210Nm
Absorption volume	- 1600cm ³ /R
min. oil passage Gs/Go	- NW16
Mass	- 137kg
max. rotations	- 30rpm

max. transverse moment: refer to 4.615.00

Volume of delivery:

2 sealing ring nr.	213
4 Connex pin	SG 22x30

Connections:

R1,R2: turn rotator		G 1/2"
Go: open grab		G 1"
Gs: close grab		G 1"
L: Measuring conn.		G 1/4"

oil distributor flange dimension 3

Edition 0310 Th.

Paint: black primary coat
 Reserve made to modifications
 All rights reserved