

Variente of design 1

Stator with centre \varnothing 90mm
(Through employment the disk 2.605.09
can change in Variante of design 2
at sheet 4.605.02)

Machine:

e.g.hydraulic excavator service weight:
max. 10ts with floating attachment
max. 6ts with rigid attachment

Add-on units:

Clamshell buckets of max. 0,6m³
 Grapples of max. 0,25m³
 Grabs for demolition and sorting
 of max. 0,3ts dead load
 Sorting units (please ask manufacturer)

Technical details:

max. thrust load	= 50 KN
max. radial load	= 34 KN
Pmax. grab	= 350bar
Pmax. rotating engine	= 250bar
max. torque /250bar	= 1250Nm
Absorption volume	= 350cm ³ /R
min. oil passage Gs/Go	= NW10
Mass	= 40kg
max. rotations	= 30rpm

max.transverse moment: refer to E 4.605.00




Volume of delivery:

4 Connex pin SG 13x30

Special accessories

at desire with grab schack valves
delivered - refer 4.605.04

Connections:

R1,R2: turn rotator		M 18x1,5
Go: open grab		M 18x1,5
Gs: close grab		M 18x1,5

Edition **101** Gm.

Paint: black primary coat

Reserve made to modifications

All rights reserved